



OLYMPIC MAXIMUM® Deck, Fence, Siding Semi-Transparent Stain

GENERAL DESCRIPTION

OLYMPIC MAXIMUM Deck, Fence & Siding Semi-Transparent Stain provides a subtle color that allows wood's natural grain and texture to show through. Core shell hybrid resin technology provides deep stain penetration, waterproofing and UV defense to strengthen, protect and condition wood fibers, ensuring the wood's natural beauty lasts.

Recommended for use on properly prepared exterior wood, including decks, fences, siding, railings, outdoor furniture, and other wood surfaces. May be used on new, dry, pressure-treated wood, uncoated new or weathered wood, or wood previously stained or painted.

RECOMMENDED SUBSTRATES

Exterior wood surfaces	New wood
Decks	Pressure-treated wood
Siding	Weathered wood
Fences	Outdoor furniture

FEATURES / BENEFITS

Stain + Sealant in One - protect and beautify in one step
Enhanced Waterproofing Protection
Advanced SunBlock® UV Defense
Extends Color Life
Exclusive Scuff Guard® Technology
Provides Our Best Mildew-Resistant Coating
Easy Water Cleanup

APPLICATION INFORMATION

Stir thoroughly before and occasionally during use. When using more than one can of the same color, intermix to ensure color uniformity.

Pretest: Apply to a small area and allow to dry to ensure acceptable appearance and penetration.

Application Equipment: Apply with a high quality polyester brush, roller, paint or stain pad, or by spray equipment.

Application Method: Apply one thin coat. When spraying or rolling, always backbrush for best results. To help avoid lap marks, apply to only a few boards at a time keeping a wet edge. Some colors, or drastic color changes, may require an additional coat to achieve a uniform finish.

Thinning: Do not thin.

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	35 to 90°F	2 to 32°C
Substrate:	35 to 90°F	2 to 32°C

PRODUCT INFORMATION

79550	Neutral Base*
79551	716 Cedar Naturaltone
79552	717 Redwood Naturaltone
79553	Clove Brown
79557	Cape Cod Gray

*Must be tinted before use.

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

PRODUCT DATA

PRODUCT TYPE:	Acrylic Oil
VOLUME SOLIDS*:	18% +/- 2%
WEIGHT SOLIDS*:	20% +/- 2%
VOC*:	96 g/L (0.8 lbs./gal.)

WEIGHT/GALLON*: 8.5 lbs. (3.8 kg) +/- 0.2 lbs. (91 g)

*Product data calculated on 79552.

COVERAGE: Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 Liters) depending upon wood texture.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Normally dries in 24 hours when applied in temperatures of 50°F (10°C) to 85°F (29°C). High humidity or low temperature application may prolong drying and recoating times. It is not recommended to apply product if rain is expected within 24 hours.

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

CLEANUP: Clean brushes and tools with warm soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

OLYMPIC MAXIMUM Deck, Fence, Siding Semi-Transparent Stain**GENERAL SURFACE PREPARATION**

Proper surface preparation is essential for the *OLYMPIC* limited warranty to apply. Surface must be clean, dry and free of all dust, dirt, mildew, oil, loose wood fibers and other contaminants. Remove loose, peeling stain or paint by sanding, scraping or wire brushing. Prior to stain application, clean weathered, dirty, or mildewed surfaces with *OLYMPIC* Deck Cleaner. After rinsing, ensure surface is free of standing water. Remove grade stamps or pencil marks by sanding.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

DECKS, FENCES OR SIDING: Clean weathered, dirty or mildewed surfaces with *OLYMPIC* Deck Cleaner prior to applying product.

PRETEST: Test a small hidden area prior to application to ensure acceptable appearance and penetration.

EXTRACTIVE BLEEDING: Some woods, such as cedar and redwood, contain high amounts of tannin, a colored wood extract. The first coat of stain may show some color discoloration, but the tannins will be trapped in the first coat of stain. A second coat will result in a uniform appearance.

LIMITATIONS OF USE

Apply when air and surface temperatures are 35°F (2°C) or above and when the air and surface temperatures will remain above 35°F (2°C) for the next 24 hours. Avoid staining in direct sunlight or on hot surfaces. It is not recommended to apply product if rain or snow is expected within 24 hours. **FOR EXTERIOR USE ONLY.**

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

Do not use on metallic, masonry, or interior surfaces.

PROTECT FROM FREEZING.

SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

PACKAGING

1-Quart (946 mL)

1-Gallon (3.78 L)

Not all products available in all sizes.

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *OLYMPIC*, *OLYMPIC* design, *MAXIMUM*, *SunBlock* and *Scuff Guard* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



Olympic - US
PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.olympic.com

Technical Services
1-800-426-6306

Architect/Specifier
1-888-PPG-IDEA

Olympic - Canada
PPG Canada, Inc.
Architectural Finishes
4 Kenview Blvd
Brampton, ON L6T 5E4

T.D. 79550 10/2012
(Supersedes 8/2011)